



ALTERNATOR PERFORMANCE DATA

RPM	Output Amps (28V) (HOT)	Output Amps (14V) (HOT)
2000	0	15
2500	4	24
3000	12	29
3500	20	32
4000	26	34
4500	31	35
5000	33	36
5500	35	37
6000	38	38
7000	41	39
8000	43	40
9000	44	41
10000	45	41

WEIGHT: 5.72 LBS.
MAX STATOR TEMP: 375° F
FOR USE ON AND20000 ACCESSORY PAD.

UNLESS OTHERWISE SPECIFIED			B & C Specialty Products P.O. Box 8, Newton, Kansas 67114	
DIMENSIONS ARE IN INCHES TOLERANCES ARE: DECIMAL 0.0XX = ± 0.03 DECIMAL 0.00X = ± 0.010 ANGLES = ±0.5 DEGREES			TITLE ENVELOPE DRAWING SD20 ALTERNATOR 14/28 VOLT, 20 AMP	
	NAME	DATE	DRAWING NO. SD20	
ENGINEER	NUCKOLLS	8-31-95	REVISION C	
DRAWN	DLS	8-31-95	DATE 11/3/05	
CHECKED			SCALE	
PROJECT			JOB NO.	
			SHEET 1 OF 1	